Calculation of the intensity distribution and energy concentration in the diffraction image of a point source

G.I. Greisukh [1], E.G. Ezhov [1], S.A. Stepanov [1]
[1] Penza State Academy of Architecture and Civil Engineering

Abstract

The article presents a technique for assessing the quality of an image generated by an optical system under unremovable aberrations in its pupils. The assessment is performed according to the integral characteristics of the dot image.

Keywords: diffraction image, image generated, optical system.

Citation: Greisukh GI, Ezhov EG, Stepanov SA. Calculation of the intensity distribution and energy concentration in the diffraction image of a point source. Computer Optics 2002; 24: 43-47.

Access full text (in Russian)

References

[1] Grammatin AP. Dependence of the energy concentration in a point image on aberrations, defocusing, and screening on square areas. J Opt Technol 2000; 67(9): 816-817.

[2] Bobrov ST, Greisukh GI. Cross-correlation of numerical criteria for assessing the image quality. Optika i Spektroskopiya; 1985; 58(5): 1068-1073.

[3] Bobrov ST, Greisukh GI, Turkevich YG. Optics of diffractive elements and systems [In Russian]. Leningrad: "Mashinostroenie" Publisher; 1986.

[4] Greisukh GI, Bobrov ST, Stepanov SA. Optics of diffractive and gradient-index elements and systems. Bellingham, WA: SPIE Press; 1997.

[5] Born M, Wolf E. Principles of optics: Electromagnetic theory of propagation, interference and diffraction of light. 7th ed. Cambridge: Cambridge University Press; 1999.

[6] Rodionov SA. About isoplanatism in arbitrary optical systems [In Russian]. Optika i Spektroskopiya 1979; 46(3): 566-573.

[7] Stavroudis ON. The optics of rays, wavefronts and caustics. New York: Academic Press; 1972.

[8] Sharma A. Computing optical path length in gradient-index media: a fast and accurate method. Appl Opt 1985; 24(24): 4367-4370.